



WIPE NEW[®] CERAMIC LIQUID WAX

DESCRIPTION AND USES

Wipe New[®] Ceramic Liquid Wax is an easy to use liquid wax that intensifies color while leaving a high gloss shine on your vehicles finish. This durable coating helps resist build-up of dirt and dust and helps protect your vehicles paint from harsh UV rays.

PRODUCT FEATURES

- Delivers maximum shine and a highly reflective finish
- Polishing agents help fill-in minor swirl marks
- Excellent UV protection
- Easy to use – wipe on, wipe off. No buffing

PRODUCT

DESCRIPTION	SKU
16 oz.	381385

PRODUCT APPLICATION

DIRECTIONS

(Read entire directions and warnings prior to use.)

1. Shake well. Be sure vehicle surface is cool to the touch. Do not apply in direct sunlight.
2. Wash, rinse and dry car just before application as dirt and other contaminants could result in a subpar finish.
3. Apply a small amount of Wipe New Ceramic Liquid Wax to a foam applicator and working in a 2ft x 2ft section, evenly apply product to vehicle paint, using overlapping motion to ensure complete coverage.
4. Immediately remove with a premium microfiber towel. Do not let coating dry. Switch to a clean towel as needed.

For maximum durability, let cure fully. Coating will attain full strength in 12 hours, but can be exposed to light rain right after application.

NOTE: If needed, use damp microfiber towel to even-out any streaks. Alternatively, re-apply product to even-out any spots. Check compatibility in an inconspicuous test-area before applying to the entire vehicle.

PHYSICAL PROPERTIES

		CERAMIC LIQUID WAX
Pigment Type		NA
Fill Weight		16 oz.
Solvents		Water
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	10 minutes
	Handle	10 minutes
	Full Cure	1 hour
Shelf Life		2 years
Flash Point		>200°F
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.